



Original Issue Date: 10.18.20

Revision Number: 0

Revision Date: 0

Enclosures: N/A

Recommended Change for AutoFil™ Pressure Gauge

Pathway Polymers conducted extensive testing on pressure gauges on the AutoFil Recycler System. Based on our comparison test of pressure readings from (1) inside the tire, (2) at the fill gun and (3) at the pump, it was concluded that the pressure readings at all three locations were identical with no discernable time lag between the readings. Based on this finding and the knowledge of several experienced AutoFil Dealers, we have converted a few current AutoFil customers over to the pressure gauge at the pump only. This seems to work well and should eliminate any isolator problems.

Therefore, we recommend that the tire pressure gauge at the fill gun be eliminated and moved to the A-Side pipe at the pump. The isolator will no longer be required but the pressure button will still need to be used.



For Additional Information

If you would like more information about Pathway Polymers or TyrFil, please contact your Pathway Polymers representative or visit our website, www.pathwaypolymers.com.

Fernando Bedos	International	423-402-1945
Robert Conkle	Product Manager	423-697-0407
Jim Hall	West	423-385-5042
Flip Hershey	Northeast	423-304-1873
Pat McKinney	South	423-385-5423
Ben Parish	Midwest	423-385-5845
Rex Slack	Southeast	423-802-6729
Lance Hanson	Technician	423-883-4566
Jeff Little	Technician	423-779-7714